


Item No.	CMS-N517-SDL	Product Name:	5MP PoE Network Bullet Camera
Product Picture			
Features			
<ul style="list-style-type: none"> ◆ CAMA Smart APP ◆ 5MP Full-Color Video & Audio PoE Network Camera ◆ Light indicator for network status(This feature is limited to non-PoE models) ◆ Spotlight on Motion Detection ◆ Full-Color with Dual Smart Illumination ◆ Support Humanoid Detection ◆ Built-in Mic and Speaker ◆ With built-in PoE ◆ Equipped With unique VQC (Video Quality Catalyst) Technology ◆ Support 512GB SD Card 			
Specifications			
Video	Image Sensor	1/3" CMOS Sensor	
	Max Resolution	2560x1792	
	Effective Pixels	5.0MP	
	Compression Standard	H.264/H.265	
	Framerate	25fps	
	Bitrate	Main Stream: 317Kbps ~ 8Mbps; Sub Stream: 68Kbps~2728Kbps	
	SNR (dB)	52dB	
	Min. Illumination	0Lux (light ON)	
Lens	Interface Type	M12	
	Lens	3.6mm, 6mm	
	FOV	3.6mm:H 80°, V 41.1°, D 94.6°; 6mm:H 49.7°, V 26.6°, D 57.3°	
Function	Audio Codec	G.711U/G.711A (default)	
	Exposure Control	Auto	
	White Balance	Auto	
	Gain Control	Auto	
	Digital 3D Noise Reduction	Support	
	OSD Information Setting	Large font OSD, OSD flashing on alarm, OSD position settings	
	SNTP	Support	
	Schedule Reboot	Support	
	Smart Defog	Support	
	Motion Detection	Support Humanoid Detection	
	Image Setting	Support Saturation, Brightness, Contrast, Sharpness adjustment	
	Image Style	Standard, Soft, Transparent	
	Day and Night Function	Auto, Always Black & White, Always Color, Scheduled Color	
	Privacy Mask	Support up 8 areas	
	Night Vision Optimization	Support	
WDR	Support		

Function	Screen Settings	Screen mirroring, Screen flipping
	IP Adaptation	Support automatic adaptation of IP address (Optional)
	Intelligent Analysis	Support Region Intrusion Detection, Line Crossing Detection, Video Blocking Detection, People Counting
	Alarm Method	Email Alarm, Client Alarm
	Remote Operation	System, Audio and Video, Image, Alarm, Network management, Storage management, Intelligent Analysis
	Audio Function	Built-in Mic and Speaker
	SD Card	Support 512GB
	VQC Technology	Support
Network	Ethernet	10/100Mbps Ethernet
	Stream	2x Streams
	Network Protocols	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
	ONVIF	Standard ONVIF
	Network Transmission	CloudSEE 2.0
	Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
	User	Up to 13 Users
	App	Support iOS/Android
General	Lights	4 White LEDs + 4 IR LEDs
	IR Distance	Up to 30 Meters
	Waterproof Level	IP67
	Power Supply	DC12V or PoE (IEEE802.3af)
	Power Consumption	<3W (During Day); <6W (At Night)
	Working Temperature	-20°C ~ 60°C
	Working Humidity	10% ~ 90% Rh
	Color/Material	White/Plastic+Metal
	Dimensions (W x H x D)	95x95x175mm
	Weight	290g
	Installation Method	Wall or ceiling mount (Bracket Optional)