


Item No.	CMS-N915-ADL	Product Name:	3MP PoE Network Bullet Camera
Product Picture			
Features			
<ul style="list-style-type: none"> ◆ CAMA Smart APP ◆ 3MP Dual Light Video & Audio PoE Network Camera ◆ Dual Smart Illumination ◆ Support Motion Detection (Humanoid) ◆ Built-in Mic ◆ Built-in PoE ◆ IP67 			
Specifications			
Video	Image Sensor	1/2.9" CMOS Sensor	
	Max Resolution	2304x1296	
	Effective Pixels	3.0MP	
	Compression Standard	H.264/H.265	
	Framerate	20fps	
	Bitrate	Main Stream: 256Kbps ~ 4Mbps; Sub Stream: 68Kbps~1024Kbps	
	SNR (dB)	39dB	
	Min. Illumination	0Lux (light ON)	
Lens	Interface Type	M12	
	Lens	2.8mm, 3.6mm	
	FOV	2.8mm:H 96°, V 53°, D 110°; 3.6mm:H 83.8°, V 42.7°, D 100.1°	
Function	Audio Codec	G.711U/G.711A (default)	
	Exposure Control	Auto	
	White Balance	Auto	
	Gain Control	Auto	
	Digital 3D Noise Reduction	Support	
	OSD Information Setting	Large font OSD, OSD flashing on alarm, OSD position settings	
	SNTP	Support	
	Schedule Reboot	Support	
	Smart Defog	Support	
	Motion Detection	Support (Humanoid)	
	Image Setting	Support Saturation, Brightness, Contrast, Sharpness adjustment	
	Image Style	Standard, Soft, Transparent	
	Day and Night Function	Auto, Always Black & White, Always Color, Scheduled Color	
	Privacy Mask	Support up 8 areas	
	Electronic Screen Setting	Support maximum and minimum exposure time setting	
	Night Vision Optimization	Support	
WDR	Support		

Function	Screen Settings	Screen mirroring, Screen flipping
	IP Adaptation	Support automatic adaptation of IP address (Optional)
	Alarm Method	Email Alarm, Client Alarm
	Remote Operation	System, Audio and Video, Image, Alarm, Network management
	Audio Function	Built-in Mic
Network	Ethernet	10/100Mbps Ethernet
	Stream	2x Streams
	Network Protocols	HTTP, TCP/IP, UDP, ICMP, RTSP, RTP, RTCP, SMTP, DHCP, DNS
	ONVIF	Standard ONVIF
	Network Transmission	CloudSEE 2.0
	Browser	IE8+, Chrome18+, Firefox5.0+, Safari5.02+
	User	Up to 13 Users
	App	Support iOS/Android
General	Lights	4 White LEDs + 4 IR LEDs
	IR Distance	Up to 40 Meters
	Waterproof Level	IP67
	Power Supply	DC12V or PoE (IEEE802.3af)
	Power Consumption	<3W (During Day); <6W (At Night)
	Working Temperature	-40°C ~ 60°C
	Working Humidity	10% ~ 90% Rh
	Color/Material	Black and White/Plastic+Metal
	Dimensions (W x H x D)	67x74x201mm
	Weight	250g
	Installation Method	Wall or ceiling mount