


Item No.	CMS-ND7608-HP	Product Name:	8 Channel NVR Host
Product Picture			
Features			
<ul style="list-style-type: none"> ◆ 8CH H.265 4K NVR ◆ Adopt the new VStar GUI, easy to operate and run smoothly. ◆ Support intelligent coding VSmart, greatly reducing storage space. ◆ Improved compatibility for hard disks, and up to 10TB. ◆ Supports multiple intelligent analyses such as motion detection, regional intrusion, tripwire detection, passenger flow statistics, scene changes, and occlusion alarms. ◆ Support the preview, storage and playback of 4K HD network video. ◆ Support built-in speakers, realize real-time monitoring of video recording, support voice alarm. 			
Specifications			
Video and Audio	IP Camera Input	8Channel	
	Audio Input/Output	IPC Audio input/Audio output through HDMI	
	Built-in Speaker	Support	
	Bandwidth I/O	80Mbps/80Mbps	
Display	Interface	1 HDMI, 1 VGA	
	Resolution	HDMI: 3840×2160@30Hz / 2560×1440@30Hz / 1920×1080 1440×900 / 1280×1024 / 1280×720 / 1024×768	
		VGA: 1920×1080,1440×900,1280×1024,1280×720,1024×768	
	Max Decoding	1CH 4K 15fps; 8CH@ 5.0MP / 4.0MP / 1080P / 960P / 720P 25fps	
	Multi-screen Display	1/4/5/6/7/8/9	
OSD	Camera Name & Time, Recording, Alarm Detecting, Remote connection, Volume, Channel Number		
Recording	Compression	H.265/H.264	
	Resolution	1CH 4K; 8CH 5.0MP / 4.0MP / 1080P / 960P / 720P	
	Record Mode	Manual, Schedule, MD	
Video Detection and Alarm	Trigger Events	Recording, Snapshot, PTZ, Voice, E-mail, Client, Buzzer	
	Video Detection	Motion Detection, No Video Detection	
Playback and Backup	Sync Playback	1CH 4K,1CH 5.0MP, 1CH 4.0MP, 1CH 3.0MP, 2CH 1080P	
	Search Mode	Channel number / recording type / date	
	Playback Function	Day View, Hour View, Back Step, Rewind, Pause, Play, Fast Forward, Slow Step, Full Screen, Snap, Sound On/Off, Zoom	
	Backup Mode	FAT32 USB Device/Network	
Network	Interface	1 RJ-45 port (10/100Mbps)	
	Network Function	TCP/IP, DHCP, UDP, SMTP, NTP	
	Smart Phone	iPhone, Android	
	Interoperability	ONVIF 2.4	

Storage	SATA	1 SATA interfaces
	Capacity	up to 10TB
General	Power Supply	DC 12V
	Consumption	≤ 10 W (Without HDD)
	Working Temperature	-10°C ~ 55°C
	Working Humidity	10% ~ 90% Rh
	Dimensions (W x H x D)	260X47.5X225mm
Weight	≤ 1.0kg (Without HDD)	